



全国统一服务热线: 400-1199-021

[首页](#) [条码产品](#) [条码行业](#) [条码方案](#) [条码知识](#) [下载中心](#) [联系我们](#)

条码应用方案:

[人事考勤条码系统](#)

[条码在大型仓库中的应用](#)

[利用条码防伪防串货](#)

[条码在无线网络中的运用](#)

[二维条码应用在物流中](#)

[条码采集器打造ERP基础](#)

[条码打印机>>>](#)

[美国intermec条码打印机](#)

[日本Tec条码打印机](#)

[美国Zebra条码打印机](#)

[日本Sato条码打印机](#)

[日本Ring条码打印机](#)

[美国Datamax条码打印机](#)

[日本Toshiba条码打印机](#)

[中国台湾Godex条码打印机](#)

[中国台湾TSC条码打印机](#)

[日本Citizen条码打印机](#)

[日本shinseia条码打印机](#)

[韩国Woosim条码打印机](#)

[德国CAB条码打印机](#)

[美国Printronix条码打印机](#)

[条码扫描器>>>](#)

[数据采集器>>>](#)

[无线局域网>>>](#)

[条码标签>>>](#)

[条码碳带>>>](#)

[条码软件>>>](#)

[条码检测仪>>>](#)

[条码打印机配件>>>](#)

[Rfid电子标签>>>](#)

## Zebra TTP 8300条形码打印机



The TTP 8300 series kiosk printers offer 300-dpi resolution for extremely sharp, full-format A4 or letter-size printouts of forms, bank statements, maps, or Web pages. The fast, compact, and low-maintenance design makes the printer ideal for unattended environments. The pull detector and jam-preventing loop presenter provide trouble-free operation. The retract function keeps sensitive documents from being left behind outside the kiosk—and it saves media. If a printout is not taken from the printer, the output will be retracted and the remaining information can be deleted from the print queue, eliminating unwanted print jobs. The TTP 8300 is available in three configurations for flexible kiosk integration: standard, compact, and vertical, each equipped with standard USB and parallel interfaces. For additional configuration flexibility, the media can be mounted either behind or below the printer.

### Standard Features

USB and IEEE-1284 interfaces

### Printer Specifications

Resolution 300 dpi (12 dots/mm)

Print width 8.5" (216 mm)

Print length Letter: 11" (279 mm) A4: 11.7" (297 mm)

Print speed 2.60" (66 mm)/sec

### Media Characteristics

Maximum roll diameter 9.84 (250 mm)

Core diameter 1" (25 mm)

Media thickness .002" (.054 mm) to .004" (.1 mm)

Media types continuous, fanfold

### Operating Characteristics

Operating temperature DT: Operating temperature 32° F (0° C) to 122° F (50° C) Direct thermal

Storage temperatures 4° F (-20° C) to 140° F (60° C)

Operating humidity 35-75% non-condensing R.H.

Storage humidity 10-90% non-condensing R.H.

Electrical 24 VDC, ± 10%, average 6 A, peak 12 A

Agency approvals UL cUL CE

### Physical Characteristics

Width 11.3" (286 mm)

Height 3.07" (78 mm)

Depth 6.73" (171 mm)

Weight 10.58 lbs (4.8 kg)

### Related Products

#### Options

Paper near end sensor

weekend paper low sensor

RS-232 Serial interface

Communication and Interface Capabilities

Parallel IEEE-1284 and USB

Optional external RS-232 Serial

Windows and Linux drivers. Direct addressing with ESC sequences.

Bar Codes/Symbolologies

Linear

Code 39

Fonts and Graphics

Up to eight bitmap fonts

[首页](#) · [条码产品](#) · [条码行业](#) · [条码方案](#) · [条码知识](#) · [下载中心](#) · [联系我们](#)

电话: 021-51088451 51088452 传真: 021-50935062

地址: 上海市浦东大道1097号15号楼4E室 邮编: 200135 邮箱: mail@jahone.com.cn

版权所有 © 2011 上海全亨条码