

全国统一服务热线 400-1199-021

[首页](#) [条码产品](#) [条码行业](#) [条码方案](#) [条码知识](#) [下载中心](#) [联系我们](#)

条码应用方案：
[人事考勤条码系统](#) [条码在无线网络中的运用](#)
[条码在大型仓库中的应用](#) [二维条码应用在物流中](#)
[利用条码防伪防串货](#) [条码采集器打造ERP基础](#)

[条码打印机>>>](#)

[条码扫描器>>>](#)

[美国Intermec条码扫描器](#)

[美国Symbol条码扫描器](#)

[意大利Datalogic条码扫描器](#)

[美国HHP条码扫描器](#)

[日本Opticon条码扫描器](#)

[美国Metrologic条码扫描器](#)

[台湾Gyoung条码扫描器](#)

[美国PSC条码扫描器](#)

[美国microscan条码扫描器](#)

[台湾CipherLAB条码扫描器](#)

[日本DENSO条码扫描器](#)

[福建新大陆条码扫描器](#)

[数据采集器>>>](#)

[无线局域网>>>](#)

[条码标签>>>](#)

[条码碳带>>>](#)

[条码软件>>>](#)

[条码检测仪>>>](#)

[条码打印机配件>>>](#)

[Rfid电子标签>>>](#)

Intermec SD61 条码扫描器



The SD61 allows you to more easily manage your Bluetooth scanners. This secure connection acts as a gateway to your host PC for up to 7 Intermec Bluetooth scanners. The SD61 houses the drivers to interact with the host PC, which means users need only scan the identifying bar code on the scanner to associate to the station and the host PC.

Features

Easy set up – No need to install new software into your PC or host systems
 Lower acquisition costs – 1 base can connect up to 7 scanners
 Reliable wireless communication through Intermec advanced communication protocol
 Increased productivity and maneuverability by working up to 100m (328 ft) away from the base (open air)
 Investment protection with a wide choice of host connections
 Industrial grade – Intermec's rugged construction is ideal for warehouse & industrial applications
 Experience the flexibility to communicate with the Bluetooth? SD61 and SF51 Intermec Scanners

Environment

Operating Temperature :-20°C/-4°F to 60°C/140°F
 Storage Temperature :-40°C/-40°F to 70°C/158°F
 Humidity :95% at 45°/113°F (non-condensing)
 Vibration and Shock protection :8G, from 10Hz to 500Hz, 2hr/axis, 3 axis
 Drop Survival :26 drops from 1.2m/3.9ft to concrete
 Sealing :IP53

Physical Characteristics

Height :3.6cm (1.4 in.)
 Width :10.2cm (4 in.)
 Depth :11.5cm (4.5in.)
 Weight :150g (5.2oz)

Power

SD61 is powered via a host or universal 5 volt power supply; depending on the cable choice. 75mA at 5V +/- 10%

[首页](#) · [条码产品](#) · [条码行业](#) · [条码方案](#) · [条码知识](#) · [下载中心](#) · [联系我们](#)

电话：021-51088451 51088452 传真：021-50935062

地址：上海市浦东大道1097号15号楼4E室 邮编：200135 邮箱：mai@jahone.com.cn

版权所有 © 2011 上海全亨条码