



全国统一服务热线 400-1199-021

[首页](#)
[条码产品](#)
[条码行业](#)
[条码方案](#)
[条码知识](#)
[下载中心](#)
[联系我们](#)

条码应用方案:
 [人事考勤条码系统](#)
[条码在无线网络中的运用](#)
[条码在大型仓库中的应用](#)
[二维条码应用在物流中](#)
[利用条码防伪防串货](#)
[条码采集器打造ERP基础](#)

[条码打印机>>>](#)

[条码扫描器>>>](#)

[美国Intermec条码扫描器](#)

[美国Symbol条码扫描器](#)

[意大利Datalogic条码扫描器](#)

[美国HHP条码扫描器](#)

[日本Opticon条码扫描器](#)

[美国Metrologic条码扫描器](#)

[台湾Gyoung条码扫描器](#)

[美国PSC条码扫描器](#)

[美国microscan条码扫描器](#)

[台湾CipherLAB条码扫描器](#)

[日本DENSO条码扫描器](#)

[福建新大陆条码扫描器](#)

[数据采集器>>>](#)

[无线局域网>>>](#)

[条码标签>>>](#)

[条码碳带>>>](#)

[条码软件>>>](#)

[条码检测仪>>>](#)

[条码打印机配件>>>](#)

[Rfid电子标签>>>](#)

Intermec SR61B条码扫描器



Intermec's SR61B incorporates industry-standard Bluetooth radio technology into a cordless handheld scanner perfect for stand-alone wireless data collection interfacing to Bluetooth-enabled hosts in rugged, industrial environments. The SR61B is available with linear imaging, area imaging, MEMS-based laser, or the unparalleled near/far area imaging.

Features

Interfaces with Intermec terminals and personal computers
 Choice of linear imager, area imager, or standard range laser scan options
 Easy configuration and personalization
 Industrial durability stands up to harsh environments

Environment

Operating Temperature :-20°C to +50°C (-4°F to +122°F)
 Storage Temperature :-40°C to +70°C (-90°F to +158°F)
 Recharging Temperature :0°C to +35°C (32°F to +95°F)
 Humidity :0 to 95% RH, Non-condensing
 Vibration and Shock protection :SAE Specification J1399 Class 3 (off road vehicle)
 Environmental Protection :IP54
 Drop Survival :26 drops onto concrete or steel surface from a height of 1.98 meters (6.5 feet)
 Ambient light :Works in any lighting conditions from 0 to 100,000 lux

Physical Characteristics

Length :17.78 cm (7 in)
 Width :6.99 cm (2.75 in)
 Depth :11.43 cm (4.5 in)
 Weight :
 (Cordless version with battery):425 gm (15 oz)
 (Cabled version without cable):280 gm (10 oz)

Power

Battery type/Supply :(Cordless) Lithium-ion
 Battery Life :(Cordless) 10+ hours per full charge
 Recharging Time :(Cordless) 2.5 hours for 90% charge
 Cables :Cabled versions are powered via host or universal 5 volt power supply

[首页](#) · [条码产品](#) · [条码行业](#) · [条码方案](#) · [条码知识](#) · [下载中心](#) · [联系我们](#)

电话: 021-51088451 51088452 传真: 021-50935062

地址: 上海市浦东大道1097号15号楼4E室 邮编: 200135 邮箱: mai@jahone.com.cn

版权所有 © 2011 上海全亨条码